






701 Osage Street, Unit 120, Denver, CO 80204 USA
Phone 303.892.0400 Toll Free 800.333.4234 Fax 303.825.5988
EMail info@bisonip.com Web www.bisonip.com




B11
1/16" (1.6 mm) FLEXIBLE SHIM
5-7/8" (149 mm) DIAMETER
USED FOR SLOPE COMPENSATION,
SOUND DAMPENING, AND/OR
FINAL LEVELING. STACK NO MORE
THAN 2 SHIMS.




PS1
1/8" (3.2 mm) RIGID SHIM
5-7/8" (149 mm) DIAMETER
USED FOR SLOPE COMPENSATION
AND/OR FINAL LEVELING. STACK NO
MORE THAN 2 SHIMS.




VT18 / VT316
1/8" (3.2 mm) OR 3/16" (4.5 mm) TABS
4-11/16" (119 mm) DIAMETER
USED FOR LOW CAVITY HEIGHTS
AND/OR SURFACE MATERIAL SPACING.



HD25-18 / HD25-316
1/4" (6 mm) FIXED HEIGHT
STACKABLE PEDESTAL
5-7/8" (149 mm) DIAMETER
1/8" (3.2 mm) OR 3/16" (4.5 mm) TABS
USED FOR LOW CAVITY HEIGHTS.
STACK UP TO 4 FIXED HEIGHT
PEDESTALS TOGETHER.




HD50-18 / HD50-316
1/2" (13 mm) FIXED HEIGHT
STACKABLE PEDESTAL
5-7/8" (149 mm) DIAMETER
1/8" (3.2 mm) OR 3/16" (4.5 mm) TABS
USED FOR LOW CAVITY HEIGHTS.
STACK UP TO 4 FIXED HEIGHT
PEDESTALS TOGETHER.



HD75-18 / HD75-316
3/4" (19 mm) FIXED HEIGHT
STACKABLE PEDESTAL
5-7/8" (149 mm) DIAMETER
1/8" (3.2 mm) OR 3/16" (4.5 mm) TABS
USED FOR LOW CAVITY HEIGHTS.
STACK UP TO 4 FIXED HEIGHT
PEDESTALS TOGETHER.

GENERAL NOTES: APPLY TO ALL OF THE ABOVE PRODUCTS

1. INSTALLATION MUST BE COMPLETED IN ACCORDANCE WITH BISON INNOVATIVE PRODUCTS SPECIFICATIONS.
2. DRAWINGS NOT TO SCALE.
3. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.BisonIP.com



SHIMS AND FIXED HEIGHT PEDESTALS

STACKABLE PEDESTALS FROM 1/4" TO 3"