



Dependability and Reliability

July 2023

SCREWJACK ADJUSTABLE PEDESTALS

- Bison's patented original ScrewJack pedestal
- Trusted brand and proven performance since 1994
- Pedestal bracing system for additional stability and heights over 24 inches
- Fast and easy installation promotes labor savings
- Screw-to-adjust pedestals ensure perfectly level decks
- Impervious to water, mold, and freeze/thaw cycles
- Unique patented design
- Sold exclusively through Oldcastle Westile



©2013-2023 United Construction Products, Inc. All Rights Reserved. Covered by one or more patents or pending patents.

Specifications

- Supports 1000 lbs (454 kg) FoS:3 per pedestal
 Pedestal tab width 3/16 inch (4.5 mm)
- Adjustable system height range is 1 ½ to 36 inches (32 to 914 mm)
 Bison Brace System required for 24 to 36 inches (610 to 914 mm)
- Accessories available for heights from 1/8 to 1 ¼ inches (3.2 to 57 mm)
 Pedestals made of high density copolymer polypropylene
 Contains 20% post-industrial recycled material

	Model No.	Description	Range	Notes	
	В1	Adjustable Pedestal	1-1/4" to 2" (32 to 51 mm)		
Pedestals	B2	Adjustable Pedestal	2" to 3" (51 to 76 mm)		
	В3	Adjustable Pedestal	3" to 4-3/4" (76 to 121 mm)		
	В4	Adjustable Pedestal	4-3/4" to 7-3/4" (121 to 197 mm)		
	C4	Coupler	Adds up to 4" (102 mm)	Screw C4 into B3 or B4 base or another C4 to reach up to 36" (914 mm)	
Accessories	VT316	Ultra Low Height Pedestal	1/8" (3.2 mm)		
	HD25-316 HD50-316 HD75-316	Fixed Height Stackable Pedestals	1/4" (6 mm) 1/2" (13 mm) 3/4" (19 mm)	Stack up to 4 Supports 1250 lbs (567 kg) FoS:3 per Pedestal	
	B11	Flexible Shim	1/16" (1.5 mm)		
	PS1	Rigid Shim	1/8" (3.2 mm)		
	LD4	Base Leveler	Adds 1/4" (6 mm)	Stack up to 4 total to base of Pedestals for 1/4" per foot (2%) slope compensation each	
	FS-1	Wood Tile Fastening Kit	Fastens Wood Tiles to Adjustable Pedestals with long so and HD50 or HD75 Fixed Height Pedestals with short so		
	FS-12 FS-12-WT	12" Fastening Spline 3/16" (4.5 mm) Tab	Fastens Wood Tiles or Paver Trays to Adjustable Pedestals with long screw, and HD50 or HD75 Fixed Height Pedestals with short screw		
	JS	Joist Saddle Attachment	Adds 1/2" (13 mm)	Works with 2 x and 4 x lumber alone or on any Bison Pedestal	
	FIB	Floating Insulation Base		/16" (305 x 305 x 17 mm) stems with 20 to 40 psi insulation	
	FFB	Floating Foundation Base		/4" (305 x 305 x 6 mm) use over soil	

IMPORTANT: Refer to ScrewJack product specifications to ensure proper use and installation. For more information visit www.bisonip.com.

I i ott i i i i i i i i i i i i i i i i i										
	n n	the street of min at the co	in his text	4 / 24 / 7 / 10 / 10	in in the second	n n				
			····		1 / 11115					
	ᅵᠿᆛᆛᆛᆛᆛ	ᅵᇊᆛᆛᆛᆛᆛᆛ		xxxxx /////	773	<u> </u>				
					\$ 24.11	7				
H		~		~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~						
	'	'	'	'						
FIXED HEIGHT PEDESTALS ADJUSTABLE PEDESTALS										
FIXED REIGHT PEDESTALS	ADJUSTABLE PEDI	ADJUSTABLE PEDESTALS								
HD50 HD75	B1	B2	B3	B4	B3 + C4	B4 + C4				
(1/2") (3/4")	(1-1/4" to 2")	(2" to 3")	(3" to 4-3/4")	(4-3/4" to 7-3/4")	(7-3/4" to 9")	(9" to 12")				
* * *	, ,	` ,	(5 (5 . 5/1)	(. 5, . 50 / 5, .)	(, 5, . 10)	(5 65 12)				
NOTE: Pedestals each shown with one optional LD4 slope compensation accessory.										